

HOW TO GENERATE A SOIL MOISTURE CHARACTERISTIC USING THE WP4C

Contributors

A <u>moisture release curve</u>, also known as a <u>soil moisture characteristic</u>, relates the <u>water potential</u> of a particular soil to its water content. This information is important for describing water storage in soil and <u>water availability</u> to plants, and for predicting water and contaminant transport in soil.

A moisture characteristic is obtained by measuring <u>water potential</u> and <u>water</u> <u>content</u> on a set of <u>soil samples</u> having a range of water contents. The following procedure can be used to generate a moisture characteristic using the <u>WP4C</u>.

The soil moisture characteristic is hysteretic. At a given <u>water potential</u>, samples which reached that water potential by wetting will have lower water content than those which reached it by drying. The procedure described here is for a wetting characteristic.

PROCEDURE

- 1. Measure the mass of a clean, stainless steel WP4C sample cup (M_{ℓ}) .
- 2. Mix an appropriate amount of soil and water to obtain the desired water content.
- 3. Seal the sample using one of METER's disposable plastic lids.
- 4. Perform steps 1-3 for various water contents. If the mixing is done in large quantity, the mixed soil can be used for numerous samples of the same water content.
- 5. Let the samples equilibrate for at least 16 hours.
- 6. Measure the water potential of each sample and then immediately measure the mass of the wet soil and sample cup $(M_{_{\!M}})$. This should be done quickly so that no moisture is lost to the air between the water potential measurement and weighing.

- 7. Place each sample with their lids off in a drying oven. Leave them in the oven for at least 16 hours at 105 degrees Celsius. When the samples are removed, immediately place the samples in a desiccator to prevent the collecting of any moisture from the air. The cups are cool after 10 to 15 minutes.
- 8. As soon as the samples are cool, measure the mass of the dry soil and sample cup (Md). The water content (g/g) can be calculated using the following equation:

$$(g/g) = \frac{M_w - M_d}{M_d - M_c}$$

9. The resulting data can then be plotted in a spreadsheet as shown in Figure 1.

NOTES

- 1. Although not necessary, the equilibration of the sample can be improved if the seal on the sample cup is somewhat airtight. This can be accomplished by using a square of Parafilm between the lid and sample cup or by sealing the perimeter of the lid with an impermeable tape.
- 2. The mixing of the soil is easiest if it is done in a large quantity (15 or more grams) and then added to the sample cup. The more finely the soil is mixed, the more reliable and consistent the results will be.
- 3. If the desired water content range is unknown, begin with an air-dry sample and increase the water content of successive samples in increments of .05 g/g or less until the soil becomes saturated.



Figure 1. Sample moisture release curve for Walla Walla silt loam using the WP4C Dew Point PotentiaMeter*

*This line is power law fit to the data.

WANT TO UNDERSTAND MORE ABOUT RELEASE CURVES?

In this 20-minute <u>webinar</u>, learn how to use a moisture release curve to analyze individual soil behaviors with respect to water. Discover:

- The relationship between water content and water potential
- What a moisture release curve is
- What a curve can tell you about your soil
- How to interpret moisture release curve data
- What you can do with the data

TAKE OUR SOIL MOISTURE MASTER CLASS

Six short videos teach you everything you need to know about soil water content and soil water potential—and why you should measure them together. Plus, master the basics of soil hydraulic conductivity.

Watch it now

GET EXPERT ADVICE

Need help? METER scientists have over 100 years combined experience measuring soil hydraulic and physical properties.

Get the "Researcher's complete guide to water potential"

REQUEST A QUOTE

CONTACT US